

# FRAMED LightPanel™ System


The **FRAMED** LightPanel™ System was designed for finished applications where the LED light panel would be visible and a finished profile is required.

The **FRAMED** LightPanel™ offers finished aluminum profiles starting at 1/4" thin. This unique design provides an ultra-slim sheet of light with a finished aluminum edge to offer quick solutions for applications where time is of the essence.


The **FRAMED** LightPanel™ can be used in a number of behind the scenes and production applications:

**Branding, Logos and Signage, Backlit Artwork, Retail, Healthcare, Residential, Commercial Interior, Custom Fixtures, Artistic Lit Walls and Art Installation.**


## ALUMINUM FRAME OPTIONS AVAILABLE:



**C SHAPED CHANNEL  
FRAME 7/16"**



**J SHAPED CHANNEL  
FRAME 5/16"**



**J SHAPED CHANNEL  
FRAME 1/4"**



## General Specifications

### LIGHT WEB TECHNOLOGY™:

3D etched patterns to evenly distribute light throughout the panel. Patterns available are GRID, DOT and MICRODOT™

### MAXIMUM SIZE:

- (A) 157" X 63" - 13'-1" X 5'-3"
- (B) 118" X 78" - 9'-10" X 6'-6"

### MINIMUM SIZE:

1" X 2" (Ideal for Cove and Accent Lighting)

### THICKNESS:

\*Thickness is determined by frame profile and shape

### LONG LIFE:

Over 50,000 hours = Nearly 12 years based on 12 hours a day. Once installed, the LightPanel™ System is virtually maintenance free.

### WATTAGE:

4.3 W/Ft. - 12V / 24V Standard Power  
5 W/ Ft. - 24V - High Power

\*ask eos specialist for information on 4400k, RGB, RGBW and Color Tuning options.

### POWER OUTPUT:

12VDC or 24VDC

### INPUT VOLTAGE:

100V TO 480V

### DIMMABLE:

The system is dimmable to <10% when matched with Dimmable Power Supplies  
\*hardwired MLV, 0-10V, or remote control plug in.

### LEDs:

ANSI Binned LEDs from Tier 1 Suppliers

LED CRI > 80

LED CRT - 2400K - 7500K

### DAMP LOCATION:

All panels are Damp Location Rated when driven with a Class 2 Power Supply

### HOSPITAL AND MRI SAFE:

The system contains non ferrous materials, making the LightPanel™ safe for MRI suites. The LightPanel™ Power supply must be installed remotely, up to 30 feet from the application.

### SERVICE AND INSTALLATION:

Field Serviceable, typically LEDs can be replaced in the field. The LightPanel™ System can be predrilled by our production team with customer's specifications.



## Optional Specifications

### FRAMING OPTIONS:

Frame profiles J and C shapes. Powder Coating for custom colors is available upon request.

### MULTIPLE PANEL MOUNTING OPTIONS:

- a. Z Clips
- b. Stand Offs
- c. Pre-Drilled
- d. All are drillable on site
- e. Key-Hole Frames
- f. Mirror Clips
- g. Pendant Cable Mounts

### COLOR TEMPERATURES:

2400K	4800K
2700K	5300K
3000K	6500K
3500K	7500K
4000K	UV (Ultraviolet)
4400K	

### ALUMINUM FRAME PROFILE OPTIONS:

- C Shaped Channel Frame (7/16" Total Thickness)
- J Shaped Channel Frame (1/4" and 5/16" total thickness).

### ADDITIONAL FEATURES:

Standard 12V / 24V Standard Power or 24V High Power depending on the application

### COMPATIBLE POWER SUPPLIES:

DMX-Compatible  
 DALI Accessible  
 Magnetic Low Voltage  
 Remote Control In-Line Dimmer  
 0-10V Dimmable  
 Electronic Static

### APPROVALS AND CERTIFICATIONS:

The LightPanel™ System is UL listed for Architectural applications and UL recognized for signage. All power supplies are UL / ETL listed.



# Product Specification Ordering Form

NAME:	PROJECT NAME:	ADDRESS:
-------	---------------	----------

PHONE:	PROJECT LOCATION:	CITY:
--------	-------------------	-------

EMAIL:	ANTICIPATED DELIVERY DATE:	ZIP CODE:
--------	----------------------------	-----------

COMPANY NAME:	PROJECT ARCHITECT:	FREIGHT METHOD:
---------------	--------------------	-----------------

	A	B	C1	C2	D	E	F	G	H	I	J	K	L	M
QTY	PANEL TYPE	LED POWER	DIMENSIONS (INCHES) TOP SIDE		COLOR TEMP	DIFFUSER	WATER-PROOF	LED SIDES	CORD COLOR	CORD LENGTH	UL RATING	CORD LOCATION	POWER SUPPLY	IF CURVED PANEL SPECIFY RADIUS (INCHES)
5	LP	SP-12V	48	50	2700	NO	YES	4SL	BC	ST	UL	TL	DHW	20

**EXAMPLE:**

A	-	B	-	C1	x	C2	-	D	-	E	-	F	-	G	-	H	-	I	-	J	-	K	-	L	-	M	SITE VOLTAGE:
↓		↓		↓	x	↓		↓		↓		↓		↓		↓		↓		↓		↓		↓		↓	
LP	-	SP-12V	-	108	x	60	-	2700	-	NO	-	YES	-	4SL	-	BC	-	ST	-	UL	-	TL	-	DHW	-	20	

**KEY:**

**A. PANEL TYPE**

- LP - BASIC** LightPanel™
- LF - FRAMED**  
LightPanel™ with C Channel 7/16"  
LightPanel™ with J1 Channel 1/4"  
LightPanel™ with J2 Channel 5/16"
- LF - MEDIA FRAME**  
GRAPHIX LightPanel™ -3/4" x 3/4"  
SLIM IMAGEART LightPanel™ -1 - 3/8" x 15/16"  
IMAGEART LightPanel™ -1 - 3/8" x 1 - 1/4"  
WINDOW LightPanel™ with Square Profile  
ACRYLIC LightPanel™ with Clear Acrylic Frame  
MAGNETIC LightPanel™ with Magnetic Frame  
FABRIK LightPanel™ eos Fabric Light Box  
SKY LightPanel™ - Suspended Frame
- CP - CRYSTAL** LightPanel™
- CF - CRYSTAL** LightPanel™ with C Channel 7/16"


**B. LED POWER**

- SP-12V** - 12V Standard Power
- SP-24V** - 24V Standard Power
- HP-12V** - 12V High Power
- HP-24V** - 24V High Power

**C. DIMENSIONS (GENERATED BY CLIENT)**

- C1**- Top Dimension
- C2**- Side Dimension

\* For shapes indicated below, shapes that are not illustrated are considered custom and require CAD



**D. COLOR TEMP**

- 2400** - 2400K
- 2700** - 2700K
- 3000** - 3000K
- 3500** - 3500K
- 4000** - 4000K
- 4400** - 4400K
- 4800** - 4800K
- 5300** - 5300K
- 6500** - 6500K
- 7500** - 7500K
- UV** - Ultraviolet
- RGB** - Color Changing
- RGBW** - Color Changing + White
- CT**- Color Tuning

**E. OPTIONAL 2MM DIFFUSION COVER**

- Y**-Yes
- N**-No

**F. WATERPROOF**

- Y**-Yes
- N**-No

**G. LED SIDES**

- 1SL** - One Side
- 2SL** - Two Sides
- 3SL** - Three Sides
- 4SL** - Four Sides

**H. POWER CORD COLOR**

- BC** - Black
- WC** - White

**I. POWER CORD LENGTH**


- ST** - Standard -9.8 ft.
- CT** - Custom Length \_\_\_\_ ft.

**J. UL RATING**

- UL** - Architectural Lighting
- UR** - Signage

**K. POWER CORD EXIT**

- TL** - Top Left Corner
- TR** - Top Right Corner
- STL** - Side Top Left Corner
- STR** - Side Top Right Corner
- BL** - Bottom Left Corner
- BR** - Bottom Right Corner
- SBL** - Side Bottom Left Corner
- SBR** - Side Bottom Right Corner



**L. POWER SUPPLY INFO**

- PI** - Plug In, DC Jack
- DPI** - Dimmable Plug in w/ remote
- HW** - Hardwired, Bare
- DHW** - Dimmable Hardwired
- REM** - RGB Remote Control
- DMX** - DMX /DALI
- 0-10V** - 0-10V Dimmable Hardwire
- MAG** - Magnetic Dimmable Hardwire

**M. CURVED LightPanel™ Radius**

\*Indicate Radius in inches

