



# GRAPHIX MEDIA FRAME


The **GRAPHIX MEDIA FRAME** LightPanels™ are designed to give designers options to display graphics and media.

The **GRAPHIX MEDIA FRAME** LightPanel™ is a Snap Frame that accomadates graphics and promotional signage and materials. The media graphics are backlit by evenly distributed light for beautiful displays that promote product or display artwork.

The **GRAPHIX MEDIA FRAME** LightPanel™ may be used for a variety of applications that include:

Branding, Logos, Signage, Custom Fixtures, Custom Art Display, Hospitality, Retail, Healthcare, Residential, Bars , Restaurants and Commercial Interior.


## General Features




**GRAPHIX MEDIA FRAME CORNER FRONT DETAIL**





**GRAPHIX MEDIA FRAME CORNER BACK DETAIL**




**GRAPHIX MEDIA FRAME CROSS SECTION**



**GRAPHIX MEDIA FRAME MOUNTING BRACKET**




STANDARD POWER




HIGH POWER

VISIBLE GRAPHIC AREA



LAYOUT SCHEME



## General Specifications (LightPanel™ Only)

### LIGHT WEB TECHNOLOGY™:

3D etched patterns to evenly distribute light throughout the panel. Patterns available are GRID, DOT and MICRODOT™

### MAXIMUM SIZE:

The maximum size is determined by the frame size  
78" x 39" / 157" x 23"

### MINIMUM SIZE:

4" X 4"

### THICKNESS:

1/4" to 7/16"

\*Thickness is determined by panel shape

### LONG LIFE:

Over 50,000 hours = Nearly 12 years based on 12 hours a day. Once installed, the LightPanel™ System is virtually maintenance free.

### WATTAGE:

4.3 W/Ft. - 12V / 24V Standard Power

5 W/ Ft. - 24V - High Power

\*ask eos specialist for information on 4400k, RGB, RGBW and Color Tuning options.

### POWER OUTPUT:

12VDC or 24VDC Standard and High Power

### INPUT VOLTAGE:

100V TO 480V

### DIMMABLE:

The system is dimmable to <10% when matched with Dimmable Power Supplies  
\*hardwired MLV, 0-10V, or remote control plug in.

### LEDs:

ANSI Binned LEDs from Tier 1 Suppliers

LED CRI > 80

LED CRT - 2400K - 6500K

### DAMP LOCATION:

All panels are Damp Location Rated when driven with a Class 2 Power Supply

### HOSPITAL AND MRI SAFE:

The system contains non ferrous materials, making the LightPanel™ safe for MRI suites. The LightPanel™ Power supply must be installed remotely, up to 30 feet from the application.

### APPROVALS AND CERTIFICATIONS:

The LightPanel™ System is UL approved.

All power supplies are UL / ETL listed.





## Optional Specifications

### ILLUMINATED FACES:

Single and Dual-Sided Illumination.

\*Dual-Sided Illumination  
GRAPHIX MEDIA FRAME available upon request.

### TAPING OPTIONS:

Reflective Tape and Tapeless Options for applications that require a seamless design

### COLOR TEMPERATURES:

- 2400K      4800K
- 2700K      5300K
- 3500K      6500K
- 4000K      7500K UV (Ultraviolet)
- 4400K      RGB, RGBW and Color Tuning

### ADDITIONAL FEATURES:

Standard 12V / 24V Standard Power or 12V / 24V High Power depending on the application and color temperature selected.

### COMPATIBLE POWER SUPPLIES:

- DMX-Compatible
- DALI Accessible
- Magnetic Low Voltage
- Remote Control In-Line Dimmer
- 0-10V Dimmable
- Electronic Static



# Product Specification Ordering Form

NAME:	PROJECT NAME:	ADDRESS:
PHONE:	PROJECT LOCATION:	CITY:
EMAIL:	ANTICIPATED DELIVERY DATE:	ZIP CODE:
COMPANY NAME:	PROJECT ARCHITECT:	FREIGHT METHOD:

	A	B	C1	C2	D	E	F	G	H	I	J	K	L	M
QTY	PANEL TYPE	LED POWER	DIMENSIONS (INCHES) TOP SIDE		COLOR TEMP	DIFFUSER	WATER-PROOF	LED SIDES	CORD COLOR	CORD LENGTH	UL RATING	CORD LOCATION	POWER SUPPLY	IF CURVED PANEL SPECIFY RADIUS (INCHES)
5	LP	SP-12V	48	50	2700	NO	YES	4SL	BC	ST	UL	TL	DHW	20

**EXAMPLE:**

A	-	B	-	C1	x	C2	-	D	-	E	-	F	-	G	-	H	-	I	-	J	-	K	-	L	-	M	SITE VOLTAGE:
↓		↓		↓		↓		↓		↓		↓		↓		↓		↓		↓		↓		↓		↓	
LP	-	SP-12V	-	108	x	60	-	2700	-	NO	-	YES	-	4SL	-	BC	-	ST	-	UL	-	TL	-	DHW	-	20	

**KEY:**

**A. PANEL TYPE**


- LP - BASIC** LightPanel™ (use for CURVED Panel as well)
- LF - FRAMED**  
LightPanel™ with C Channel 7/16"  
LightPanel™ with J1 Channel 1/4"  
LightPanel™ with J2 Channel 5/16"
- LF - MEDIA FRAME**  
GRAPHIX LightPanel™ -3/4" x 3/4"  
SLIM IMAGEART LightPanel™ -1 - 3/8" x 15/16"  
IMAGEART LightPanel™ -1 - 3/8" x 1- 1/4"  
WINDOW LightPanel™ with Square Profile  
ACRYLIC LightPanel™ with Clear Acrylic Frame  
MAGNETIC LightPanel™ with Magnetic Frame  
FABRIK LightPanel™ eos Fabric Light Box  
SKY LightPanel™ - Suspended Frame
- CP - CRYSTAL** LightPanel™
- CF - CRYSTAL** LightPanel™ with C Channel 7/16"

**B. LED POWER**

- SP-12V** - 12V Standard Power
- SP-24V** - 24V Standard Power
- HP-12V** - 12V High Power
- HP-24V** - 24V High Power

**C. DIMENSIONS (GENERATED BY CLIENT)**

- C1**- Top Dimension
- C2**- Side Dimension
- \* For shapes indicated below, shapes that are not illustrated are considered custom and require CAD



**D. COLOR TEMP**

- 2400** - 2400K
- 2700** - 2700K
- 3000** - 3000K
- 3500** - 3500K
- 4000** - 4000K
- 4400** - 4400K
- 4800** - 4800K
- 5300** - 5300K
- 6500** - 6500K
- 7500** - 7500K
- UV** - Ultraviolet
- RGB** - Color Changing
- RGBW** - Color Changing + White
- CT**- Color Tuning

**E. OPTIONAL 2MM DIFFUSION COVER**

- Y**-Yes
- N**-No

**F. WATERPROOF**

- Y**-Yes
- N**-No

**G. LED SIDES**

- 1SL** - One Side
- 2SL** - Two Sides
- 3SL** - Three Sides
- 4SL** - Four Sides

**H. POWER CORD COLOR**

- BC** - Black
- WC** - White

**I. POWER CORD LENGTH**


- ST** - Standard -9.8 ft.
- CT** - Custom Length \_\_\_\_ ft.

**J. UL RATING**

- UL** - Architectural Lighting
- UR** - Signage

**K. POWER CORD EXIT**

- TL** - Top Left Corner
- TR** - Top Right Corner
- STL** - Side Top Left Corner
- STR** - Side Top Right Corner
- BL** - Bottom Left Corner
- BR** - Bottom Right Corner
- SBL** - Side Bottom Left Corner
- SBR** - Side Bottom Right Corner



**L. POWER SUPPLY INFO**

- PI** - Plug In, DC Jack
- DPI** - Dimmable Plug in w/ remote
- HW** - Hardwired, Bare
- DHW** - Dimmable Hardwired
- REM** - RGB Remote Control
- DMX** - DMX /DALI
- 0-10V** - 0-10V Dimmable Hardwire
- MAG** - Magnetic Dimmable Hardwire

**M. CURVED LightPanel™ Radius**

\*Indicate Radius in inches