



Product Specification Ordering Form

NAME:			PROJECT NAME:			ADDRESS:		
PHONE:			PROJECT LOCATION:			CITY:		
EMAIL:			ANTICIPATED DELIVERY DATE:			ZIP CODE:		
COMPANY NAME:			PROJECT ARCHITECT:			FREIGHT METHOD:		

	A	B	C1	C2	D	E	F	G	H	I	J	K	L	M	N
QTY	PANEL TYPE	VOLTAGE	DIMENSIONS (INCHES) TOP SIDE		COLOR TEMP	LED SIDES	LED POWER	POWER SUPPLY	IF CURVED PANEL SPECIFY RADIUS (INCHES)	CORD LENGTH	CORD LOCATION	CORD COLOR	UL RATING	DIFFUSER	WATER-PROOF
5	LP	24V	48	50	2700	ASL	SP	DHW	20	ST	TL	BC	UL	NO	YES

A	B	C1	C2	D	E	F	G	H	I	J	K	L	M	N
↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓
LP	24V	108	60	2700	ASL	SP	DHW	20	ST	TL	BC	UL	NO	YES

PLEASE FILL OUT THE FORM ON THE PREVIOUS PAGE USING THIS KEY AND SAMPLE ABOVE

KEY:

A. PANEL TYPE

LP - BASIC LightPanel™ (use for CURVED Panel as well)

LF - FRAMED

LightPanel™ with C Channel 7/16"
LightPanel™ with J1 Channel 1/4"
LightPanel™ with J2 Channel 5/16"

LF - MEDIA FRAME

GRAPHIX LightPanel™ -3/4" x 3/4"
SLIM IMAGEART LightPanel™ -1 - 3/8" x 15/16"
IMAGEART LightPanel™ -1 - 3/8" x 1- 1/4"

WINDOW LightPanel™ with Square Profile
ACRYLIC LightPanel™ with Clear Acrylic Frame
MAGNETIC LightPanel™ with Magnetic Frame

FABRIK LightPanel™ eos Fabric Light Box
SKY LightPanel™ - Suspended Frame

CP - CRYSTAL LightPanel™

CF - CRYSTAL LightPanel™ with C Channel 7/16"

B. VOLTAGE

12V - 12V


24V - 24V

C. DIMENSIONS (GENERATED BY CLIENT)

C1- Top Dimension

C2- Side Dimension

* For shapes indicated below, shapes that are not illustrated are considered custom and require CAD



D. COLOR TEMP

2400 - 2400K

2700 - 2700K

3000 - 3000K

3500 - 3500K

4000 - 4000K

4400 - 4400K

4800 - 4800K

5300 - 5300K

6500 - 6500K

7500 - 7500K

UV - Ultraviolet

RGB - Color Changing

RGBW - Color Changing + White

CT- Color Tuning

E. LED SIDES

1SL - One Side

2SL - Two Sides

3SL - Three Sides

4SL - Four Sides

F. LED POWER

SP- Standard Power

HP- High Power

G. POWER SUPPLY INFO

PI - Plug In, DC Jack

DPI - Dimmable Plug in w/ remote

HW - Hardwired, Bare

DHW - Dimmable Hardwired

REM - RGB Remote Control

DMX - DMX /DALI

0-10V - 0-10V Dimmable Hardwire

MAG - Magnetic Dimmable Hardwire

H. CURVED LightPanel™ Radius

*Indicate Radius in inches

I. POWER CORD LENGTH

ST - Standard -9.8 ft.

CT - Custom Length ____ ft.

J. POWER CORD EXIT

TL - Top Left Corner

TR - Top Right Corner

STL - Side Top Left Corner


STR - Side Top Right Corner

BL - Bottom Left Corner

BR - Bottom Right Corner

SBL - Side Bottom Left Corner

SBR - Side Bottom Right Corner



K. POWER CORD COLOR

BC - Black

WC - White

L. UL RATING

UL - Architectural Lighting

UR - Signage

M. OPTIONAL 2MM DIFFUSION COVER

Y-Yes

N-No

N. WATERPROOF

Y-Yes

N-No



Product Specification Ordering Form

NAME:	PROJECT NAME:	ADDRESS:
PHONE:	PROJECT LOCATION:	CITY:
EMAIL:	ANTICIPATED DELIVERY DATE:	ZIP CODE:
COMPANY NAME:	PROJECT ARCHITECT:	FREIGHT METHOD:

	A	B	C1	C2	D	E	F	G	H	I	J	K	L	M	N
QTY	PANEL TYPE	VOLTAGE	DIMENSIONS (INCHES) TOP SIDE		COLOR TEMP	LED SIDES	LED POWER	POWER SUPPLY	IF CURVED PANEL SPECIFY RADIUS (INCHES)	CORD LENGTH	CORD LOCATION	CORD COLOR	UL RATING	DIFFUSER	WATER-PROOF
5	LP	24V	48	50	2700	ASL	SP	DHW	20	ST	TL	BC	UL	NO	YES